

TP3

SS2361TCM

Tourz E-lite adopts 880pcs warm and cold white Leds,uniform color mixing, wide coverage, CCT 2700-6500K linearadjustment, CRI>98, can perfectly present the color temperature of the fixture itself, Ultraquiet waterproof fan isused for efficient heat dissipation, low noise, compact sizeand lightweight to achieve the ultimate. It is the perfectchoice for exhibition center, conference hall, show and otherperformance places.



PRODUCT PARAMETERS

Optical system

Light source 440pcsxWW,440pcsxCW	
Luminous flux 44280lm	
Beam angle 70°	Field angle 120°
CCT 2700-6500K	CRI 98

Appearance

Size	652x120x249mm	Casing	Extruded aluminum
Weight	11.3KG	Color	Black

Electrical Specs

Voltage 100-240VAC,50/60Hz
Max. Power 500W

Power Connection
Power in and out

Signal socket
3pin 5pin in and out


Control System

Dimmer 0-100% 16 Bit
Cooling Forced Convection
Protocol DMX512、RDM
Display On board Control
Personality UNO(1CHS)、VW.D(3CHS)、VW.F(6CHS)、STD.P(9CHSS)


Work Environment Certification

Ambient Temp -20°C-45°C	CE
IP Rated IP65	


ILLUMINANCE AT DISTANCE SS2361TCM



DIMENSIONS



ACCESSORIES (Accessories not included unless otherwise stated)



Barn doors
(6813100080)