

T10

SS9184SC/SC HC

T10 is a high-power professional LED profile moving ahead with 5° -50° Electronic zoom system. It is a kind of final version stage light, accurate and efficient motor can provide not only large pan angle and tilt angles but also with smooth and high speed. PLUTO 800 PROFILE has image-cutting system can cut out any polygon, and with zoom, focus, prism, color wheel, CMY, gobo wheels, iris, frost can supply high-quality beam colors and gobos. PLUTO 800 PROFILE is equipped with animation wheel which can create dynamic water and dynamic fire effect. PLUTO 800 PROFILE is designed for the cultural center, function hall, banquet hall, and rental performance market.



PRODUCT PARAMETERS

Optical system

Light source	Angle
1000Wmodule	5°-50°
CRI	
SS9184SC HC: 90Ra	
Total lumen output	Illuminance
SS9184SC: 23540lm	SS9184SC:115040Lx@5M
SS9184SC HC: 13328lm	SS9184SC HC: 55200Lx@5M

Appearance

Size	483x283x746mm	Casing	Flame-retardant plastic (V0)
Casing	35.5KG	Color	Black

Electrical Specs

Voltage	Max. Power
100-240VAC,50/60Hz	1200W
Power Connection	Signal socket
power in	3pin + 5pin in / out, RJ45 in / out

Control System

Pan/Tilt rotation	Cooling
540°/270°(8-16bit)	Forced Convection
Dimmer	
0-100%16Bit	
Display	
On board Control, Custom Mode,0-25Hz Strobe	
Control	
DMX512、RDM、SACN、ARTNET、W-DMX ((optional))	
Con Personality	
BASIC、STANDARD、EXTEND	
Special	
Pan/Tilt movement blackout, User-selectable pan/tilt ranges	

Effect synthetic system

Rotating Gobo
7 Gobos+ White, Gobo-flow effect, Gobo shake, Bi-directional rotation
Static Gobo
10 Gobos+White, Gobo-flow effect, Gobo shake
Colors
One color wheel (7 dichroic-filters+White,Rainbow-flow effect)
CMYK
CMY wheel, Linear CTO function
Framing system
4 shutter blade; Each blade's angel and direction can be individual controlled, fully blackout; The whole Framing module is ±90°.
Animation Wheel
Bi-directional rotation
Prism
One piece of 5 F prisms,bidirectional rotating, speed can be adjusted

Iris	Frost
5-100% linearly adjustable with macro	1 Frost filter
Focus	Zoom
Motorized linear focus	Motorized linear Zoom

Work Environment



Ambient Temp
0°C-45°C
IP Rated
IP20

Certification



CE、MET

ILLUMINANCE AT DISTANCE

SS9184SC



SS9184SC HC




FIXED GOBO



COLOR



Rotation Gobo



CMY+CTO



Framing System

